

TR HANK® RIVET BUSHES




TR Fastenings is recognised
throughout the industry for world class
products & services

We manufacture, stock & distribute
a vast range of industrial fasteners
& components



www.trfastenings.com
sales@trfastenings.com
Edition 7

Contents

	Page		Page
	Hexagon (HX) 3		Standoff Serrated Face (RF) 7
	Round Serrated Spigot (RH) 4		Mini Standoff Serrated Face (MF) 8
	Round Serrated Face (HK) 4		Swage Nut (XX) 9
	Mini Round Serrated Face (RM) 5		Round Euro (RD) 10
	Tank (TA) 6		Mini Round Euro (MI) 11

Standard Wire Gauge Sizes - Applies to non-Euro rivet bush items

Gauge size (SWG)	To cover sheet thickness (mm)
24	0.4 - 0.6
22	0.7 - 0.8
20	0.9 - 1.0
18	1.1 - 1.4
16	1.5 - 1.7
14	1.8 - 2.2
12	2.3 - 2.8
10	2.9 - 3.4
8	3.5 - 4.2
6	4.3 - 5.1
4	6

All data is correct to the best of our knowledge, however TR cannot be held responsible for any errors or omissions.

Price on application for any non-preferred sizes.

www.trfastenings.com

Scan to go to our website and view installation guides ▶

Hank is a registered trade mark and therefore can only be applied to goods supplied by TR Fastenings.





TR Hank® Rivet Bushes

Hexagon (HX)




Self Finish Steel | Zinc Plated Steel | Stainless Steel



Metric Dimensions

Thread		M2.5	M3	M3.5	M4	M5	M6	M8	M10	M12
Spigot Diameter +0.00 -0.13	A	5.54	5.54	6.73	6.73	7.92	9.52	12.70	15.87	19.05
Body Diameter ±0.15	B	7.92	7.92	7.92	7.92	9.52	11.10	14.27	19.05	22.22
Body Depth ±0.13	C	3.17	3.17	3.17	3.17	3.81	5.08	6.35	7.62	10.16
Recommended hole size +0.05 -0.00		5.54	5.54	6.73	6.73	7.92	9.52	12.70	15.87	19.05

Example of the Hank-Loc® feature:



Hank-Loc version available

Please note: Hank-Locking is a process applied to our standard rivet bush ranges giving them a locking feature.



www.trfastenings.com

Scan to go to our website and view installation guides


Hank is a registered trade mark and therefore can only be applied to goods supplied by TR Fastenings.

TR Hank® Rivet Bushes


Round Serrated Spigot (RH) / Round Serrated Face (HK)



Self Finish Steel | Zinc Plated Steel | Stainless Steel | Aluminium | Brass




Self Finish Steel | Zinc Plated Steel | Stainless Steel | Aluminium | Brass



Metric Dimensions

Thread		M2.5	M3	M3.5	M4	M5	M6	M8	M10	M12
Spigot Diameter +0.00 -0.13	A	5.54	5.54	6.73	6.73	7.92	9.52	12.70	15.87	19.05
Body Diameter ±0.15	B	7.92	7.92	9.52	9.52	11.10	12.70	15.87	19.05	25.40
Body Depth ±0.13	C	3.17	3.17	3.17	3.17	3.81	5.08	6.35	7.62	10.16
Recommended hole size +0.05 -0.00		5.54	5.54	6.73	6.73	7.92	9.52	12.70	15.87	19.05

Example of the Hank-Loc® feature:



Hank-Loc version available

Please note: Hank-Locking is a process applied to our standard rivet bush ranges giving them a locking feature.

www.trfastenings.com

Scan to go to our website and view installation guides ▶

Hank is a registered trade mark and therefore can only be applied to goods supplied by TR Fastenings.





TR Hank® Rivet Bushes

Mini Round Serrated Face (RM)




Self Finish Steel | Zinc Plated Steel | Stainless Steel | Aluminium | Brass



Metric Dimensions

Thread		M2	M2.5	M3	M3.5	M4	M5	M6	M8	M10	M12
Spigot Diameter +0.00 -0.13	A	3.50	4.19	4.19	5.41	5.41	6.40	7.70	9.70	12.70	15.87
Body Diameter ±0.15	B	5.00	5.50	5.50	7.00	7.00	8.50	10.00	12.00	16.00	19.00
Body Depth ±0.13	C	2.30	2.80	2.80	3.20	3.20	3.80	5.10	6.50	7.60	7.60
Recommended hole size +0.05 -0.00		3.50	4.19	4.19	5.41	5.41	6.40	7.70	9.70	12.70	15.87

Example of the Hank-Loc® feature:



Hank-Loc version available

Please note: Hank-Locking is a process applied to our standard rivet bush ranges giving them a locking feature.




www.trfastenings.com

✦ Scan to go to our website and view installation guides

Hank is a registered trade mark and therefore can only be applied to goods supplied by TR Fastenings.

Self Finish Steel | Zinc Plated Steel | Stainless Steel



Metric Dimensions

Thread		M3	M4	M5	M6	M8	M10	M12
Spigot Diameter +0.00 -0.13	A	5.54	6.73	7.92	9.52	12.70	15.87	19.05
Body Diameter ±0.15	B	7.92	9.52	11.10	12.70	15.87	19.05	25.40
Body Depth ±0.13	C	8.61	8.97	9.32	10.57	11.89	16.50	19.05
Recommended hole size +0.05 -0.00		5.54	6.73	7.92	9.52	12.70	15.87	19.05




TR Hank® Rivet Bushes

Standoff Serrated Face (RF)



Self Finish Steel | Zinc Plated Steel | Stainless Steel




Metric Dimensions

Thread		M2.5	M3	M3.5	M4	M5	M6	M8	M10	M12
Spigot Diameter +0.00 -0.13	A	5.54	5.54	6.73	6.73	7.92	9.52	12.70	15.87	19.05
Body Diameter ±0.15	B	7.92	7.92	9.52	9.52	11.10	12.70	15.87	19.05	25.40
Recommended hole size +0.05 -0.00		5.54	5.54	6.73	6.73	7.92	9.52	12.70	15.87	19.05

Length Variants

Length of body ±0.13	C	8-10mm	11-13mm	14-16mm	17-22mm
Depth of c/bore	D	3.0mm Nom	6.0mm Nom	9.0mm Nom	12.0mm Nom

Example of the Hank-Loc® feature:



Hank-Loc version available

Please note: Hank-Locking is a process applied to our standard rivet bush ranges giving them a locking feature.



www.trfastenings.com

✦ Scan to go to our website and view installation guides


Hank is a registered trade mark and therefore can only be applied to goods supplied by TR Fastenings.

TR Hank® Rivet Bushes

Mini Standoff Serrated Face (MF)



Self Finish Steel | Zinc Plated Steel | Stainless Steel




Metric Dimensions

Thread		M2	M2.5	M3	M3.5	M4	M5	M6	M8	M10	M12
Spigot Diameter +0.00 -0.13	A	3.50	4.19	4.19	5.41	5.41	6.40	7.70	9.70	12.70	15.87
Body Diameter ±0.15	B	5.00	5.50	5.50	7.00	7.00	8.50	10.00	12.00	16.00	19.00
Recommended hole size +0.05 -0.00		3.50	4.19	4.19	5.41	5.41	6.40	7.70	9.70	12.70	15.87

Length Variants					
Length of body ±0.13	C		8-10	11-13	14-16
Depth of c/bore	D		3.0 Nom	6.0 Nom	9.0 Nom

Example of the Hank-Loc® feature:



Hank-Loc version available
Please note: Hank-Locking is a process applied to our standard rivet bush ranges giving them a locking feature.

www.trfastenings.com

Scan to go to our website and view installation guides ▶

Hank is a registered trade mark and therefore can only be applied to goods supplied by TR Fastenings.




TR Hank® Rivet Bushes

Swage Nut (XX)



Self Finish Steel | Zinc Plated Steel | Stainless Steel




Metric Dimensions

Thread		M3	M4	M5	M6
Spigot Diameter +0.00 -0.13	A	4.24	5.38	6.35	8.70
Body Diameter ±0.15	B	6.35	7.92	8.70	11.05
Body Depth ±0.13	C	1.5	2.0	2.0	4.0
Recommended hole size +0.05 -0.00		4.25	5.40	6.40	8.75

The Swage Nut is the same size dimensionally as the standard Self-Clinch Nut, however the Swage Nut is inserted using the same method as the Hank Rivet Bush.

Example of the Hank-Loc® feature:



Hank-Loc version available
Please note: Hank-Locking is a process applied to our standard rivet bush ranges giving them a locking feature.





www.trfastenings.com
 ♦ Scan to go to our website and view installation guides
 Hank is a registered trade mark and therefore can only be applied to goods supplied by TR Fastenings.

TR Hank® Rivet Bushes

Round Euro (RD)



Self Finish Steel | Zinc Plated Steel




Metric Dimensions

Thread		M3	M4	M5	M6	M8
Spigot Diameter +0.00 -0.13	A	5.84	6.90	8.30	9.60	13.05
Body diameter ±0.15	B	7.92	9.52	11.10	12.70	15.87
Body Depth ±0.13	C	3.17	3.81	4.45	5.72	6.35
Recommended hole size +0.10 -0.0		5.90	6.95	8.35	9.65	13.10

Preferred Range

Thread		M3	M4	M5	M6	M8
Sheet Thickness	0.9 - 1.0	•	•	•	•	
	1.1 - 1.3	•	•	•	•	
	1.4 - 1.6	•	•	•	•	•
	2.0 - 2.2	•	•	•	•	•
	2.3 - 2.5		•	•	•	•
	2.9 - 3.1		•	•	•	•

Example of the Hank-Loc® feature:



Hank-Loc version available

Please note: Hank-Locking is a process applied to our standard rivet bush ranges giving them a locking feature.

www.trfastenings.com

Scan to go to our website and view installation guides ▶

Hank is a registered trade mark and therefore can only be applied to goods supplied by TR Fastenings.





TR Hank® Rivet Bushes

Mini Round Euro (MI)



Self Finish Steel | Zinc Plated Steel




Metric Dimensions

Thread		M3	M4	M5	M6
Spigot Diameter +0.00 -0.13	A	4.10	5.40	6.40	7.60
Body diameter ±0.15	B	5.50	7.00	8.50	10.00
Body Depth ±0.13	C	2.80	3.20	3.80	5.10
Recommended hole size +0.05 -0.00		4.20	5.50	6.50	7.70

Preferred Range

Thread		M3	M4	M5	M6
Sheet Thickness	0.9 - 1.0	•	•	•	•
	1.1 - 1.3	•	•	•	•
	1.4 - 1.6	•	•	•	•
	1.7 - 1.9	•	•	•	•
	2.0 - 2.2	•	•	•	•
	2.3 - 2.5	•	•	•	•

Example of the Hank-Loc® feature:



Hank-Loc version available

Please note: Hank-Locking is a process applied to our standard rivet bush ranges giving them a locking feature.



www.trfastenings.com

Scan to go to our website and view installation guides

Hank is a registered trade mark and therefore can only be applied to goods supplied by TR Fastenings.



UK
t: +44 (0)8454 811 800 f: +44 (0)870 458 7851
e-mail: uk@trfastenings.com

Ireland
t: +353 (0)22 22301 f: +353 (0)22 22056
e-mail: ireland@trfastenings.com

Netherlands
t: +31 (0)541 511515 f: +31 (0)541 517134
e-mail: netherlands@trfastenings.com

Norway
t: +47 67 06 70 00 f: +47 67 06 70 10
e-mail: norway@trfastenings.com

Sweden
t: +46 (0)8 578 44 900 f: +46 (0)8 578 44 950
e-mail: sweden@trfastenings.com

Spain
t: +34 93 647 22 45
e-mail: spain@trfastenings.com

Hungary
t: +36 (06)24 516970 f: +36 (06)24 516961
e-mail: hungary@trfastenings.com

Poland - Representative
t: +48 (22)402 36 14 f: +48 (22)402 36 24
e-mail: poland@trfastenings.com

Italy
t: +39 (0)75 9149015 f: +39 (0)75 9190165
e-mail: info@trvic.it

Germany
t: +49 (0) 5246 . 50320 - 0 f: +49 (0) 5246 . 50320 - 70
e-mail: info@trkuhlmann.com

Slovakia - Representative
m: +421(0)911 012 016
e-mail: slovakia@trfastenings.com

USA
t: +1 800-280-2181 f: +1 281-807-0620
e-mail: usa@trfastenings.com

Singapore
t: +65 6759 6033 f: +65 6759 6022
e-mail: singapore@trfastenings.com

Malaysia
t: +6 (03) 5519 1444 f: +6 (03) 5510 8505
e-mail: psep@psep.com.my

China
t: +86 21 5032 5696 f: +86 21 5032 5775
e-mail: china@trfastenings.com

Taiwan
t: +886 7 557 6366 f: +886 7 557 1977
e-mail: taiwan@trfastenings.com

Philippines - Representative Office
t: +63-25768476
e-mail: philippines@trfastenings.com

India
t: +91 (0)44 4280 3932
e-mail: india@trfastenings.com

Thailand
t: +66(0)2 130 6562 f: +66(0)2 130 7603
e-mail: thailand@trfastenings.com

Japan - Representative
t: +81(0)70 4467 1118
e-mail: japan@trfastenings.com

Technical and Innovation Centres

Birmingham - UK
t: +44 (0)121 521 0100 f: +44 (0)121 521 0101
e-mail: wednesbury@trfastenings.com

Gothenburg - Sweden
t: +46 (0)31 31 760 776 f: +46 (0)8 578 44 950
e-mail: sweden@trfastenings.com

CUICAR - South Carolina USA
t: +1 800 280 2181 f: +1 281 807 0620
e-mail: usa@trfastenings.com

sales@trfastenings.com

www.trfastenings.com

info@trfastenings.com



Master Distributor Details