



Flammability rating  
of UL94 V0



NEMA & UL  
Certifications



IP68 (up to 10 bar)  
and IP69K

A range of premium  
cable glands that meet  
the highest demands on  
quality

Relevant certifications will  
provide customers peace  
of mind on performance

One of the highest levels  
of ingress protection  
compared to competitors  
due to advanced seal  
design

Carries NEMA approvals:  
important when equipment  
is being supplied to  
American markets

Wide range of styles in  
the HUMMEL portfolio to  
meet specific application  
requirements

A comprehensive range  
of standards & approvals  
ensuring they meet the  
requirements of diverse  
industries

Contact TR Fastenings - Your specialist in Cable Glands



Localised stock availability



Technical & dimensional data



Design support and problem  
solving

Click on the product to view at [www.trfastenings.com](http://www.trfastenings.com)

Product Group	Range Name	Thread Sizes	Colours
 <b>Nylon</b>	HSK-K Metric	M12 - M63	Black, Grey & Blue
	HSK-K Pg	Pg7 - Pg48	Black, Grey & Blue
 <b>Flex-Protecting Nylon</b>	HSK-K-Flex Metric	M12 - M25	Black & Grey
	HSK-K-Flex Pg	Pg7 - Pg21	Black & Grey
 <b>Nylon Lock Nuts</b>	GM-FS Metric	M12 - M63	Black & Grey
	GM-FS Pg	Pg7 - Pg48	Black & Grey
 <b>Nickel Plated Brass</b>	HSK-M Metric	M12 - M63	Self
	HSK-M Pg	Pg7 - Pg48	Self
	HSK-MINI	M6 - M10 & Pg7	Self
 <b>Stainless Steel</b>	HSK-INOX Metric (1.4305)	M12 - M40	Self
	HSK-INOX Metric (1.4404)	M12 - M40	Self
	HSK-MINI-INOX Metric (1.4305)	M8 & M10	Self
 <b>Brass &amp; Stainless Steel Lock Nuts</b>	GM-Ms Metric	M12 - M63	Self
	GM-Ms Pg	Pg7 - Pg48	Self
	GM-INOX Metric	M12 - M40	Self
 <b>O-Rings - Nitrile</b>	O-Ring-NBR (Required for IP68 & 69K rating on Nylon Cable Glands)	M12 - M63	Black
		Pg7 - Pg48	



Flammability rating  
of UL94 V0



NEMA & UL  
Certifications



IP68 (up to 10 bar)  
and IP69K



part of the Trifast plc Group

# General Purpose Cable Glands & Accessories

Click on the product to view at [www.trfastenings.com](http://www.trfastenings.com)

Product Group	Range Name	Thread Sizes	Colours
 <p><b>Nylon</b></p>	Metric - standard and long mounting thread	M12 - M63 Std M12 - M40 Long	Black, Grey, Red & White
	Pg - standard and long mounting thread	Pg7 - Pg48 Std Pg7 - Pg21 Long	Black, Grey, Red & White
 <p><b>Nylon Lock Nuts</b></p>	Metric	M12 - M63	Black & Grey
	Pg	Pg7 - Pg48	Black & Grey
 <p><b>Nickel Plated Brass</b></p>	Metric	M12 - M63	Self
	Pg	Pg7 - Pg48	Self
	Mini	M6 - M16 / Pg7 - Pg9	Self
 <p><b>Stainless Steel</b></p>	INOX Metric (1.4305)	M12 - M63	Self
	INOX Pg (1.4305)	Pg7 - Pg48	Self
 <p><b>Brass &amp; Stainless Steel Lock Nuts</b></p>	Metric	M12 - M63	Self
	Pg	Pg7 - Pg48	Self
 <p><b>O-Rings - Nitrile</b></p>	O-Ring-NBR (Required for IP68 rating on Nylon Cable Glands)	M12 - M63	Black
		Pg7 - Pg48	
 <p><b>Threaded Plugs</b></p>	Metric	M12 - M40	Black & Grey
	Pg	Pg7 - Pg36	Black & Grey



Flammability rating of UL94 V2



UL Certifications



IP68 (up to 5 bar)